



| Compatible Staplers/Nailers for Teragren Flooring                   |                                     |  |                                   |                             |   |
|---|-------------------------------------|--|-----------------------------------|-----------------------------|---|
| Manufacturer of Nailer & Website                                    | Manufacturer Product Model #        | Cleat/Staple Size Used or Recommended by the MFG.                | Teragren Product Tested           | Teragren Flooring Thickness | PSI Recommendations from the manufacturer |
| <b>Bostich</b>  | <b>MIIIFS</b>                       | 1/2" crown - 1-1/2"-2" 15-1/2 gauge staple - using MIII foot kit | <b>Signature, Craftsman II</b>    | <b>15, 16, &amp; 18mm</b>   | <b>70-90</b>                              |
|   | <b>MIIIFN</b>                       | 1-1/2" & 2" 16 gauge cleat - using model MIII foot kit           | <b>Signature, Craftsman II</b>    | <b>15, 16, &amp; 18mm</b>   | <b>70-90</b>                              |
| <a href="http://www.bostitch.com">http://www.bostitch.com</a>       |                                     |  |                                   |                             |   |
| <b>PORT-A-NAILS</b>   | <b>402 Manual Porta-Nailer</b>      | 1-1/2" & 2" cleat - using model # 40248 shoe accessory           | <b>PF Signature, Craftsman II</b> | <b>15 mm</b>                | <b>NA</b>                                 |
|   |                                     |  | <b>UF Signature (FGC-FGN)</b>     | <b>16 mm</b>                | <b>NA</b>                                 |
|   |                                     |  | <b>UF Signature (VGC-VGN)</b>     | <b>18 mm</b>                | <b>NA</b>                                 |
|   | <b>421 Portamatic</b>               | 1-1/2" & 2" cleat - using model # 50230 shoe accessory           | <b>PF Signature, Craftsman</b>    | <b>15 mm</b>                | <b>90 psi</b>                             |
|   |                                     |  | <b>UF Signature (FGC-FGN)</b>     | <b>16 mm</b>                | <b>90 psi</b>                             |
|   |                                     |  | <b>UF Signature (VGC-VGN)</b>     | <b>18 mm</b>                | <b>90 psi</b>                             |
|   | <b>470 Hammerhead TL Portamatic</b> | 2" cleat - using model # 47090 shoe accessory                    | <b>PF Signature, Craftsman</b>    | <b>15 mm</b>                | <b>90 psi</b>                             |
|   |                                     |  | <b>UF Signature (FGC-FGN)</b>     | <b>16 mm</b>                | <b>90 psi</b>                             |
|   |                                     |  | <b>UF Signature (VGC-VGN)</b>     | <b>18 mm</b>                | <b>90 psi</b>                             |
|   | <b>472 Hammerhead S Stapler</b>     | 2" 15 gauge staple - using model # 47090 shoe accessory          | <b>PF Signature, Craftsman</b>    | <b>15 mm</b>                | <b>90 psi</b>                             |
|   |                                     |  | <b>UF Signature (FGC-FGN)</b>     | <b>16 mm</b>                | <b>90 psi</b>                             |
|   |                                     |  | <b>UF Signature (VGC-VGN)</b>     | <b>18 mm</b>                | <b>90 psi</b>                             |
| <a href="http://www.porta-nails.com">http://www.porta-nails.com</a> |                                     |  |                                   |                             |   |
| <b>POWERNAIL</b>  | <b>Pneumatic Model 50P</b>          | 1-1/2" long 18 gauge cleat - .200 Adapter with 1 shim            | <b>Synergy</b>                    | <b>12 mm</b>                | <b>90 psi</b>                             |
|   | <b>Manual Model 50M</b>             | 1-1/4" long 18 gauge cleat - .200 Adapter with 1 shim            | <b>Synergy</b>                    | <b>12 mm</b>                | <b>NA</b>                                 |
|   | <b>Pneumatic Model Flex</b>         | 1-1/2" long 18 gauge cleat                                       | <b>Synergy</b>                    | <b>12 mm</b>                | <b>90 psi</b>                             |
| <a href="http://www.powernail.com">http://www.powernail.com</a>     |                                     |  |                                   |                             |   |
| <b>Primatch</b>   | <b>Pneumatic Nailer Q550</b>        | 1-1/2" 18 gauge L-type nails                                     | <b>Synergy</b>                    | <b>12 mm</b>                | <b>90-95 psi</b>                          |
| <a href="http://www.primatch.ca">http://www.primatch.ca</a>         |                                     |  |                                   |                             |   |